

Croplands Equipment has been in the business of manufacturing spraying equipment since 1972. Because of this Croplands know a good sprayer when they see one, and as such are proud to be associated with the RoGator self-propelled machines. Before delivery each RoGator machine is thoroughly tested and modified to suit the demanding conditions of the Australian environment, so that you can be sure your machine will not only do the job but do it like a pro.

### CROPLANDS CREDIT

At Croplands Credit, we understand that financing is as much a part of your purchase decision as the features and benefits of the product. So we're committed to providing the best means of acquiring the equipment you need, while allowing you to preserve other credit lines of operating capital.

See your authorized RoGator dealer for:

- Competitive Rates
- Comprehensive Financing
- Flexible Payment Schedules
- Flexible Terms
- Quality Service
- Leasing Options
- Virtually Unlimited Resources

Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.

### CUSTOMER CHEMISTRY: THE RIGHT CHEMISTRY

#### Parts and Service for your Application Equipment

Croplands have parts and service mapped out – literally. Throughout Australia and New Zealand, our dedicated parts and service dealer network is ready and available with strategically located facilities to expedite your parts requirements as efficiently as possible. Add to that trained service technicians and service vehicles that are on call to handle maintenance and repairs. Not to mention the best warranty in the business.

#### Faster service. Better parts availability. More Efficiency.

The right chemistry for the best support

#### CROPLANDS CUSTOMER SERVICE

Australia 1800 999 162  
New Zealand 0800 106 898  
sales@croplands.com.au

#### CROPLANDS SALES REPRESENTATIVES

**AUSTRALIA**  
General Manager, Australasia Brendan Deck 0418 845 676  
Sales Manager, Australasia Sean Mulvaney 0409 911 544  
Central NSW/TAS Dave Farmer 0427 651 971  
WA John Griffiths 0407 132 746  
Sth NSW/Sunraysia David Hamilton 0427 975 072  
VIC Nick McCulloch 0417 832 784  
Sth QLD/Nth NSW Jeremy Rennick 0407 485 569  
FNQ/NT Jason Sims 0409 899 491  
SA Luke Wormald 0419 991 534

**NEW ZEALAND**  
North Island Greg Evans 0427 752 322  
North Island Chris Cox 0276 879 010  
South Island Rob Marshall 0272 486 822

**CROPLANDS**

www.croplands.com.au

© 2009 AGCO Corporation. AGCO® and RoGator® are registered trademarks of AGCO Corporation. CAT® is a registered trademark of Caterpillar, Inc. AGCO Corporation has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. AGCO Corporation is not responsible for differences between the specifications or illustrations contained in this publication and the actual equipment. Equipment produced by other manufacturers is shown in photographs in this brochure for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. All rights reserved. AGCO Corporation, 4205 River Green Parkway, Duluth, GA 30096.

**AGCO**  
Your Agriculture Company

RoGator® is a worldwide brand of AGCO Corporation.

# SPECIFICATIONS

ROGATOR® SPRAYERS FOR PRE- & POST-EMERGENCE APPLICATIONS | MODELS 984 • 984H • 1184 • 1184H • 1386



RoGator 984 • 984H • 1184 • 1184H • 1386 | SPECIFICATIONS

www.croplands.com.au

**CROPLANDS**

## SPECIFICATIONS COMMON TO ALL MODELS

HYDROSTAT						
Make & Model	Bosch Rexroth AA4VG					
Displacement	7.6 cu. in. (125 cc)					
WHEEL MOTOR						
Make	Sampo					
Model Front	BBC 05 with Parking Brakes					
Model Rear	BBC 05					
BRAKES						
Service	Hydrostatic Dynamic Braking					
Parking	Multiple Wet Disc on Front Wheel Motors					
FRAME						
Material	Flexible Modified Carbon Steel					
Shape	3 X 9" C Section					
Construction	Ladder-Style Bolted Cross Members					
STEERING						
Cylinders	Double-Acting					
Toe Alignment	Hydraulic Rephasing					
Turning Radius Center of Axle (2-wheel steer)	23 ft. (7 m)					
Optional GatorTrak (4-wheel steer)	13.5 ft. (4.1m)					
APPLICATION CAB						
Glass Area	60 sq. ft. (5.5 sq m)					
Floor Area	14 sq. ft. (1.3 sq m)					
Cab Suspension	Optional Air Ride Cab					
Radio	AM / FM CD with Weather Band / Satellite Ready					
HVAC	Automatic Temperature Control					
Filtration	Three-Level Activated Carbon					
Steering Wheel	14 inch Leather Wrapped					
Standard Seat	Air Ride Seat Suspension					
Optional Seat	Semi-Active Seat Suspension with Heated Seat Cushions					
AIR SYSTEM						
Compressor	Engine Mounted					
Governor	120 psi (8.2 bar)					
CFM	13.2 cfm (6.2 L/s)					
Reservoir	12.5 gal. (48 L)					
FLUID CAPACITIES						
Fuel	Hydraulic Reservoir	Engine Oil	Engine Coolant	Gear Box	Windshield Reservoir	
130 gal. (492 L)	60 gal. (227 L)	24 qt. (22.7 L)	30 qt. (32 L)	4.5 qt. (4.3 L)	1.6 qt. (1.5 L)	

## 984H

ENGINE	
Make/Model/Certification	Caterpillar C7 Tier III
Number of Cylinders	6
Horsepower	250 (186 kW) @ 2,100 rpm
Peak Horsepower	275 (205 kW) @ 1,850 rpm
Displacement	439 cu. in. (7.2L)
Torque	888 ft-lbs (1204 n-m) @ 1,400 rpm

## 984 • 1184 • 1184H

ENGINE	
Make/Model/Certification	Caterpillar C7 Tier III
Number of Cylinders	6
Horsepower	275 (205 kW) @ 2,100 rpm
Peak Horsepower	299 (223 kW) @ 1,850 rpm
Displacement	439 cu. in. (7.2L)
Torque	977 ft-lbs (1324 n-m) @ 1,400 rpm

## 1386

ENGINE	
Make/Model/Certification	Caterpillar C9 Tier III
Number of Cylinders	6
Horsepower	311 (232 kW) @ 2,100 rpm
Peak Horsepower	336 (251 kW) @ 1,900 rpm
Displacement	538 cu. in. (8.8L)
Torque	1105 ft-lbs (1499 n-m) @ 1,400 rpm

## 984H • 984 • 1184H • 1184

HYDROSTAT	
Make/Model	Bosch Rexroth Tandem AA4VG
Displacement	7.6 cu. in. (125 cc)

## 1386

HYDROSTAT	
Make/Model	Sauer Danfoss Tandem Series 90
Displacement	6.1 cu. in. (100 cc)

## 984H • 984 • 1184H • 1184

SPEED				
	1st	2nd	3rd	4th
	14 mph (22.5 kph)	18 mph (28.9 kph)	24 mph (38.5 kph)	33 mph (53.1 kph)

## 1386

SPEED				
	1st	2nd	3rd	4th
	13 mph (21 kph)	15 mph (24 kph)	17 mph (27 kph)	21 mph (34 kph)
	5th	6th		
	25 mph (40 kph)	36 mph (58 kph)		

## 984H • 1184H

ADJUSTABLE AXLE	
Outer Tube	8 in. X 8 in.
Inner Adjustable Tube	Reinforced 6 in. X 6 in.
Adjustment Range	120 in. to 152 in.
SUSPENSION	
Type	Variable Rate Leaf Spring
Fore and Aft Torque Rods	Rubber-Isolated Parallel Link
Rebound Control	Shock Absorber

## 984 • 1184 • 1386

ADJUSTABLE AXLE	
Outer Tube	8 in. X 9 in.
Inner Adjustable Tube	Reinforced 6 in. X 6 in.
Adjustment Range	120 in. to 152 in.
SUSPENSION	
Type	Air Spring
Leveling Valves	Haldex Height Control Valves
Fore and Aft Torque Rods	Rubber-Isolated Parallel Link
Rear Anti-Roll System	Modified Four Link
Rebound Control	Shock Absorber

