

Croplands Equipment has been in the business of manufacturing spraying equipment since 1972. Because of this Croplands know a good sprayer when they see one, and as such are proud to be associated with the SpraCoupe self-propelled machines. Before delivery each SpraCoupe machine is thoroughly tested and modified to suit the demanding conditions of the Australian environment, so that you can be sure your machine will not only do the job but do it like a pro.

### CROPLANDS CREDIT

At Croplands Credit, we understand that financing is as much a part of your purchase decision as the features and benefits of the product. So we're committed to providing the best means of acquiring the equipment you need, while allowing you to preserve other credit lines of operating capital.

See your authorized SpraCoupe dealer for:

- Competitive Rates
- Comprehensive Financing
- Flexible Payment Schedules
- Flexible Terms
- Quality Service
- Leasing Options
- Virtually Unlimited Resources

Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.

### CUSTOMER CHEMISTRY: THE RIGHT CHEMISTRY

#### Parts and Service for your Application Equipment

Croplands have parts and service mapped out – literally. Throughout Australia and New Zealand, our dedicated parts and service dealer network is ready and available with strategically located facilities to expedite your parts requirements as efficiently as possible. Add to that trained service technicians and service vehicles that are on call to handle maintenance and repairs. Not to mention the best warranty in the business.

#### Faster service. Better parts availability. More Efficiency.

The right chemistry for the best support

#### CROPLANDS CUSTOMER SERVICE

Australia 1800 999 162  
New Zealand 0800 106 898  
sales@croplands.com.au

#### CROPLANDS SALES REPRESENTATIVES

##### AUSTRALIA

General Manager, Australasia	Brendan Deck	0418 845 676
Sales Manager, Australasia	Sean Mulvaney	0409 911 544
Central NSW/TAS	Dave Farmer	0427 651 971
WA	John Griffiths	0407 132 746
Sth NSW/Sunraysia	David Hamilton	0427 975 072
VIC	Nick McCulloch	0417 832 784
Sth QLD/Nth NSW	Jeremy Rennick	0407 485 569
FNQ/NT	Jason Sims	0409 899 491
SA	Luke Wormald	0419 991 534

##### NEW ZEALAND

North Island	Greg Evans	0427 752 322
North Island	Chris Cox	0276 879 010
South Island	Rob Marshall	0272 486 822

**CROPLANDS**

www.croplands.com.au

© 2009 AGCO Corporation. AGCO® and RoGator® are registered trademarks of AGCO Corporation. CAT® is a registered trademark of Caterpillar, Inc. AGCO Corporation has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. AGCO Corporation is not responsible for differences between the specifications or illustrations contained in this publication and the actual equipment. Equipment produced by other manufacturers is shown in photographs in this brochure for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. All rights reserved. AGCO Corporation, 4205 River Green Parkway, Duluth, GA 30096.

# SPECIFICATIONS

SPRACOUPE® SPRAYERS FOR PRE- & POST-EMERGENCE APPLICATIONS | 4000 • 7000



4000 • 7000 | SPECIFICATIONS

SpraCoupe

www.croplands.com.au

**CROPLANDS**



SpraCoupe® is a worldwide brand of AGCO Corporation.

# 4000 SERIES

## SPECIFICATIONS

### OPTIONS:

- Belly Shields: Easy to attach and remove, belly shields protect your investment in both your crop and your machine.
- Tow Bar: Attach the optional telescoping tow bar and tow the applicator to the field.
- Crop Deflectors: Move foliage out of the tire tracks and reduce potential crop damage.
- Floodlight Kit: Light up the field for low light and nighttime operations.
- Foam Marker: Mark your field position clearly for spray swath accuracy.
- Front Axle & Drive Shaft Extension: Six-inch extensions allow 80-108 in. (203-274 cm) machines to be extended to 92-120 in. (234-304 cm).

4660	
Empty Weight – lb. (kg)	9,979 (4,526)
Operating Weight – lb. (kg)	13,823 (6,270)
Clearance – in. (cm)	Automatic: 46 (116.8)   Manual 48 (121.9)
<b>ENGINE</b>	
Make – HP	Perkins® 125
Type	1104D 4.4L / Certified EPA Non-Road Tier III
Low Idle Speed – rpm	850
Governed (full load) – rpm	2,200
Fuel	Diesel
Fuel Capacity – L	166.6
Engine Oil Capacity – L	8.5
<b>TRANSMISSION</b>	
Type	T-5, 5-speed manual or Allison 2100 RDS 5-speed automatic
Transmission Oil Capacity – L	2.65 or Allison 14
<b>SPEED RANGES</b>	
Automatic   Manual	
1st – mph (kph)	4.2 (6.8)   3.9 (6.3)
2nd – mph (kph)	7.2 (11.6)   6.8 (10.9)
3rd – mph (kph)	9.2 (14.8)   10.2 (16.4)
4th – mph (kph)	13.0 (21.9)   13.6 (21.9)
5th – mph (kph)	18.3 (29.5)   18.9 (30.4)
Reverse – mph (kph)	2.9 (4.7)   4.3 (6.9)
<b>TIRES/SUSPENSION/TRACK WIDTH</b>	
Front	9-24 8 ply, 320/85 R25
Rear (Standard)	320/85R24 12 ply, 380/85 R24, 230/95 R32
Front Suspension	Independent strut and spring suspension with oscillating front axle
Rear Suspension	Independent knee action suspension with coil spring
Track Width – in. (cm)	80 – 108 (203.2 – 259.1)
<b>SPRAYING SYSTEM</b>	
Spray Control	Raven™ 460
Product Pump	Engine-mounted, belt-driven Hypro® centrifugal pump with electromagnetic clutch
Agitation	Manual adjust with electric on/off switch in cab
Liquid Tank Capacity – L	1,514
Filtration	50 mesh
<b>BOOM</b>	
Spraying Width – ft. (m)	60 (18.3) or 80 (24.4) or 60/80 (18.3/24.4)
Sections	3 on 60', 5 on 80' and 60/80'
<b>BOOM HEIGHT</b>	
Low Position – in. (cm)	21 – 76 (533 – 1,930)
High Position – in. (cm)	37 – 92 (940 – 2,337)

7660	
Empty weight – lb. (kg)	18,000 (8,165)
Operating weight – lb. (kg)	24,000 (10,866)
Clearance – in. (cm)	48 (121.9)
<b>ENGINE</b>	
Make/HP	Perkins®/174
Type	1106D, 6.0L / Certified EPA Non-Road Tier III
Low Idle Speed	850
Governed (full load)	2500
Fuel	Diesel
Fuel Capacity – L	246.1
Engine Oil Capacity – L	13.2
<b>TRANSMISSION</b>	
Type	Caterpillar PG 115 PowerShift, 6 forward and 2 reverse speeds
Transmission Oil Capacity – gal. (L)	8.0 (30.3)
<b>SPEED RANGES</b>	
1st – mph (k/h)	6.4 (10.3)
2nd – mph (k/h)	10.0 (16.1)
3rd – mph (k/h)	13.2 (21.2)
4th – mph (k/h)	18.3 (29.5)
5th – mph (k/h)	20.8 (33.5)
6th – mph (k/h)	27.5 (44.3)
Reverse 1 – mph (k/h)	6.4 (10.3)
Reverse 2 – mph (k/h)	13.5 (21.7)
<b>TIRES/SUSPENSION/TRACK WIDTH</b>	
Front	320/85R38 (optional 540/65R24 or 380/80R38)
Rear	380/80 R46 standard (optional 320/90R46, 480/80R46, or 620/70R42)
Front Suspension	Independent strut with linear rate suspension springs and hydraulic track width adjustment
Rear Suspension	Independent "knee action" suspension incorporated into chain case design with hydraulic suspension and hydraulic track width adjustment
Track width – in. (cm)	88 – 120 (223.5-304.8) optional 120 – 152 (304.8 – 386.1)
<b>SPRAYING SYSTEM</b>	
Spray Control	Raven™ 5000 standard, optional Raven™ Viper Pro and Falcon VT
Flow Control	PWM hydraulic or product servo valve
Agitation	Manual adjust with electric on/off switch in cab
Liquid Tank Capacity – gal. (L)	724 (2,744) Poly or 660 (2,498) Stainless Steel
Rinse Tank Capacity – gal. (L)	65 (246)
Product Pump	Hypro® 9303
Filtration	50 mesh
<b>BOOMS</b>	
Spraying Width – ft. (m)	60/80 (18.3/24.4) – optional 60/90 (18.3/27.4)
Sections	5
Nozzle Spacing – in. (cm)	20 (50.8)
<b>BOOM HEIGHT – HYDRAULIC ADJUSTMENT</b>	
Low Position – in. (cm)	23 – 80 (58.4 – 203.2)
High Position – in. (cm)	39 – 96 (99.1 – 243.8)

# 7000 SERIES

## SPECIFICATIONS

### OPTIONS:

- Belly Shields: Easy to attach and remove, belly shields protect your investment in both your crop and your machine.
- Crop Deflectors: Move foliage out of the tire tracks and reduce potential crop damage.
- Work Lights: Light up the field for low light and nighttime operations.
- Foam Marker: Mark your field position clearly for spray swath accuracy.
- Tires: Choose from a variety of combinations that provide greater flotation and minimal soil compaction, while extending the spraying window in wet conditions.

